


RoHS
  无卤要求
  REACH

PIN	定义
1	LED-
2	LED+
3	GND
4	VI028
5	NC (ID)
6	NC
7	NC
8	GND
9	NC
10	NC
11	NC
12	LSAO
13	NC
14	LSDA
15	GND
16	VI01.8V
17	NC
18	LPTE
19	LSCE-B
20	NC
21	LSCK
22	NC
23	REST
24	GND
25	NC

背光电路 (5并联电路):



- NOTE:
- DISPLAY MODE : 0.9 IPS ,65K COLOR STRANSMISSIVE, NORMALLY BLACK
  - Driver IC:ST7735P3
  - Viewing Direction: ALL 0'Clock
  - Operating Temperature: -20° - +70°
  - Storage Temperature: -30° - +80°
  - Backlight Type: 2 White LEDs, 2并联
  - BL Input Current: 20 mA (ONE LED)
  - LCM Brightness: TBD cd/m TYP

如果客户做全贴合, 考虑到LCM材料公差, LCM组装公差, CTP贴合公差, CTP  
 丝印公差, 建议CTP的丝印开窗在屏AA区单边外扩0.2MM.  
 标示"\*"的尺寸为重点管控尺寸  
 未注尺寸公差: ±0.2

四线一通道

HUA XIAN JING Display Limited		www.huaxianjing.com	
MODEL NO.	TFT009B001	TITLE	SCALE 1:1
CUST. REF NO.		LCM	SHEET 1/1
DATE		DATE	Version: 1
DATE		DATE	
DATE		DATE	

PRO. (3):

REV	DESCRIPTION	DATE
△	RELEASE FOR SAMPLES	2022. 03. 23
△		
△		

REV	DESCRIPTION	DATE	CUST. REF NO.	DATE	DATE