


PIN	定义
1	GND
2	LEDK
3	VDD
4	DC
5	CS
6	SCK
7	SI
8	RESET
9	LEDA
10	NC

LCD型号/类型/分辨率	BOE0.9/IPS/128*128
视角方向	ALL
偏光片	上磨0° /下光90°
驱动IC	ST7735
LED颗数/连接方式/电流	2-LED/并联/40mA
背光底色要求	

- 技术要求:
- 带\*尺寸为重点尺寸, 带( )尺寸为参考尺寸
  - LCD切割断面崩边≤1/3 (单层LCD厚度)
  - 平面翘曲度≤0.35mm
  - 符合RoHS指令
  - 工作温度: -20℃~70℃
  - 储存温度: -30℃~80℃
  - 建议TP V. A开窗比LCD A. A单边大0.4mm
  - 泡棉开窗比LCD A. A单边大0.3mm



REV	SIGN	DESCRIPTION	PIC	DATE
A		新建	BILL	2023.05.09

PART DESCRIPTION		LCM			HUA XIAN JING Display Limited www.huaxianjing.com			
DESIGNED		UNIT	SCALE	3rd ANGLE	SIZE	SHEET NUMBER		
CHECKED		mm	1.00		A4	1 of 1		
APPROVED		PART NUMBER				DRAWING REV.		
		MODEL NAME				PART NUMBER VER.		
		TFT019B003				N/A		