


1	A
2	GND(K)
3	RESET
4	RS
5	SDA
6	SCL
7	VDD
8	CS



LCD型号/类型/分辨率	1.44/TN/128*128
视角方向	12 0° Clock
偏光片	上磨45° / 下光45°
驱动IC	ST7735S
LED颗数/连接方式/电流	1-LED/并联/20mA
背光底色要求	

- 技术要求:
- 带\*尺寸为重点尺寸, 带( )尺寸为参考尺寸
  - LCD切割断面崩边≤1/3 (单层LCD厚度)
  - 平面翘曲度≤0.35mm
  - 符合RoHS指令
  - 工作温度: -20℃~70℃
  - 储存温度: -30℃~80℃
  - 建议TP V.A开窗比LCD A.A单边大0.4mm
  - 泡棉开窗比LCD A.A单边大0.3mm

A		首次发行	XW	22, 4, 6
REV	SIGN	DESCRIPTION	PIC	DATE

PART DESCRIPTION	LCM		HUA XIAN JING Display Limited www.huaxianjing.com			
DESIGNED	UNIT mm	SCALE 1.00	3rd ANGLE	SIZE A4	SHEET NUMBER 1 of 1	
CHECKED	PART NUMBER				DRAWING REV. A	
APPROVED	MODEL NAME TFT014F025				PART NUMBER VER. N/A	