


RoHS 无卤要求 REACH

| PIN | DESCRIPTION |
|-----|-----------------|
| 1 | BL_K |
| 2 | BL_A |
| 3 | GND |
| 4 | VDD(2.8V) |
| 5 | IOVCC(1.8/2.8V) |
| 6 | TE |
| 7 | /CS |
| 8 | /RSTB |
| 9 | RS |
| 10 | WRB |
| 11 | RDB |
| 12 | DB7 |
| 13 | DB6 |
| 14 | DB5 |
| 15 | DB4 |
| 16 | DB3 |
| 17 | DB2 |
| 18 | DB1 |
| 19 | DB0 |
| 20 | GND |
| 21 | NC |
| 22 | NC |
| 23 | NC |
| 24 | NC |

FPC弯折示意图
FPC展开出货



- NOTE:
1. DISPLAY MODE : 2.4 TN ,65K COLOR STRANSMISSIVE, NORMALLY WHITE
 2. Driver IC: ILI9340X
 3. Viewing Direction: 12 O' Clock
 4. Operating Temperature: -20° - +70°
 5. Storage Temperature: -30° - +80°
 6. Backlight Type: 4 White LEDs, 4并联
 7. BL Input Current: 20 mA (ONE LED)
 8. LCM Brightness: 450 cd/m TYP

如果客户做全贴合, 考虑到LCM材料公差, LCM组装公差, CTP贴合公差, CTP丝印公差, 建议CTP的丝印开窗在屏AA区单边外扩0.2MM.
标示***的尺寸为重点管控尺寸
未注尺寸公差: ±0.2

HUA XIAN JING Display Limited www.huaxianjing.com

| REV | DESCRIPTION | DATE | CUST.REF NO. | LCM | SCALE 1:1 | UNIT : mm | Version: 1 |
|-----|---------------------|------------|--------------|------|-----------|-----------|------------|
| △ | RELEASE FOR SAMPLES | 2022.03.17 | DRAWN BY | DATE | | | |
| △ | | | CHECKED BY | DATE | | | |
| △ | | | APPROVE BY | DATE | | | |

PROJ.(3):