


1	LEDA
2	LEDK
3	GND
4	RESET
5	VSYNC
6	HSYNC
7	CLK
8	DEN
9	GND
10	R4
11	R3
12	R2
13	R1
14	R0
15	G5
16	G4
17	G3
18	G2
19	G1
20	G0
21	B4
22	B3
23	B2
24	B1
25	B0
26	IOVCC
27	SDI
28	SCL
29	CS
30	VCC

- 技术要求:
- 带*尺寸为重点尺寸, 带()尺寸为参考尺寸
 - LCD切割断面崩边 $\leq 1/3$ (单层LCD厚度)
 - 平面翘曲度 $\leq 0.35\text{mm}$
 - 符合RoHS指令
 - 工作温度: $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$
 - 储存温度: $-30^{\circ}\text{C} \sim 80^{\circ}\text{C}$
 - 建议TP V.A开窗比LCD A.A单边大0.4mm
 - 泡棉开窗比LCD A.A单边大0.3mm



LCD型号/类型/分辨率	QV032DE0-N80/IPS/379*960
视角方向	ALL
偏光片	上磨0°/下光90°
驱动IC	GC9503VC
LED颗数/连接方式/电流	6-LED/串联/20mA
背光底色要求	

PART DESCRIPTION	LCM	HUA XIAN JING Display Limited www.huaxianjing.com				
DESIGNED		UNIT mm	SCALE 1.00	3rd ANGLE	SIZE A4	SHEET NUMBER 1 of 1
CHECKED		PART NUMBER				DRAWING REV. A
APPROVED		MODEL NAME TFT031B008				PART NUMBER VER. N/A

REV	SIGN	DESCRIPTION	PIC	DATE
		首次发行	RSF	2022.02.28