


FPC弯折示意图
FPC弯折出货



BLU CIRCUIT DIAGRAM
IF=20mA VF=2.8-3.2V

PIN No.	SYMBOL
1	RESET
2	DB7
3	DB6
4	DB5
5	DB4
6	DB3
7	DB2
8	DB1
9	DB0
10	RS
11	CS
12	WR
13	RD
14	K
15	K
16	A
17	A
18	VCC
19	VCC
20	GND
21	GND
22	NC
23	NC
24	TE

LCD型号/类型/分辨率	3.5/1IPS/320*480
视角方向	ALL
偏光片	上磨砂0° /下光90°
驱动IC	ST7796U
LED颗数/连接方式/电流	6-LED/6并/120mA
背光底色要求	

- 技术要求:
- 带*尺寸为重点尺寸, 带()尺寸为参考尺寸
 - LCD切割断面崩边≤1/3(单层LCD厚度)
 - 平面翘曲度≤0.35mm
 - 符合RoHS指令
 - 工作温度: -20℃~70℃
 - 储存温度: -30℃~80℃
 - 建议TP V.A开窗比LCD A.A单边大0.4mm
 - 泡棉开窗比LCD A.A单边大0.3mm

REV	SI GN	DESCRIPT ION	PI C	DATE
A		首次发行	XW	2022.5.20

PART DESCRIPTION		LCM		HUA XIAN JING Display Limited www.huaxianjing.com			
DESIGNED		UNIT	SCALE	3rd ANGLE	SIZE	SHEET NUMBER	
CHECKED		mm	1.00		A4	1 of 1	
APPROVED		PART NUMBER				DRAWING REV.	
		MODEL NAME				PART NUMBER VER.	
		TFT035B044				A N/A	