


PIN:	SYMBLE
1	MIC+/NC
2	MIC-/NC
3	GND
4	SPK+/NC
5	SPK+/NC
6	SPK-/NC
7	SPK-/NC
8	GND
9	ID
10	TE
11	GND
12	TDN2
13	TDP2
14	GND
15	TDN0
16	TDP0
17	GND
18	TCN
19	TCP
20	GND
21	TDN1
22	TDP1
23	GND
24	TDN3
25	TDP3
26	GND
27	RST
28	NC
29	VDD2V8
30	VDD101V8
31	LEDK
32	LEDA
33	GND
34	VTCX0/NC
35	BPI_BUS11/NC
36	BPI_BUS12/NC
37	NC
38	VIBR/NC
39	NC




	R1	R2	ID电压
1	20k	3.3k	0.4V
2	25k	10k	0.8V
3	68k	51k	1.2V

LCD型号/类型/分辨率	BOE/5.5/IPS/720*1280
视角方向	ALL
偏光片	上砂0°/下增亮90°
驱动IC	ILI9881C
LED颗数/连接方式/电流	12-LED/6串2并/40mA
背光底色要求	

FPC弯折示意图  
FPC弯折出货

以下问题请确认是否OK  
 1: 第1, 2, 4, 5, 6, 7,  
 34, 35, 36, 38 PIN是定义否OK? 不接  
 2: ID电路是否OK? 选用哪组电阻? 第一组  
 3: AA区位置是否ok?  
 4: 厚度是否ok?

- 技术要求:
- 带\*尺寸为重点尺寸, 带 ( ) 尺寸为参考尺寸
  - LCD切割断面崩边≤1/3 (单层LCD厚度)
  - 平面翘曲度≤0.35mm
  - 符合RoHS指令
  - 工作温度: -20℃~70℃
  - 储存温度: -30℃~80℃
  - 建议TP V.A开窗比LCD A.A单边大0.4mm
  - 泡棉开窗比LCD A.A单边大0.3mm



REV	SIGN	DESCRIPTION	PIC	DATE
		增加双面胶	KZH	2023.10.08
		改下增亮片	KZH	2023.08.23
A		首次发行	KZH	2023.06.15

PART DESCRIPTION		HUA XIAN JING Display Limited			
LCM		www.huaxianjing.com			
DESIGNED		UNIT	SCALE	3rd ANGLE	SHEET NUMBER
CHECKED		mm	1.00		1 of 1
APPROVED		PART NUMBER			DRAWING REV.
		MODEL NAME	TFT055B005		A
					PART NUMBER VER.
					N/A