



NO	SYMBOL
1	NC
2	NC
3	SDA
4	SCL
5	RS
6	RES
7	CS
8	GND
9	NC
10	VCC
11	LEDK
12	LEDA
13	GND

LCD型号/类型/分辨率	BOE1.06/96*160
视角方向	12点钟
偏光片	EWV片0.22上砂45° /下光45°
驱动IC	ST7735P3
LED颗数/连接方式/电流	1-LED/20mA
背光底色要求	

- 技术要求:
- 带\*尺寸为重点尺寸, 带 ( ) 尺寸为参考尺寸
  - LCD切割断面崩边≤1/3 (单层LCD厚度)
  - 平面翘曲度≤0.35mm
  - 符合RoHS指令
  - 工作温度: -20℃~70℃
  - 储存温度: -30℃~80℃
  - 建议TP V.A开窗比LCD A.A单边大0.4mm
  - 泡棉开窗比LCD A.A单边大0.3mm

PART DESCRIPTION	LCM	HUA XIAN JING Display Limited www.huaxianjing.com				
DESIGNED		UNIT mm	SCALE 1.00	3rd ANGLE	SIZE A4	SHEET NUMBER 1 of 1
CHECKED		PART NUMBER				DRAWING REV. A
APPROVED		MODEL NAME TFT106B012				PART NUMBER VER. N/A

REV	SIGN	DESCRIPTION	PIC	DATE
		更新IC型号原7735S	KZH	2022.6.24
A		首次发行	XW	2022.1.4