


FPC展开出货

QSPI

PIN	NAME
1	LEDK
2	LEDA
3	VDD3V3
4	VDD3V3
5	VDD3V3
6	GND
7	TE
8	CLK
9	GND
10	CS
11	RES
12	SPI3
13	SPI2
14	SPI1
15	SPIO
16	GND

LCD型号/类型/分辨率	BOE1.32/IPS/360*360
视觉方向	ALL
贴片方式	上细砂0° /下增亮90°
驱动IC	ST77916
LED颗数/连接方式/电流	2LED/并联/40mA



LED CIRCUIT DIAGRAM:

- 技术要求:
- 未标注尺寸公差±0.20MM
 - LCD切割断面崩边≤1/3 (单层LCD厚度)
 - 平面翘曲度≤0.35mm
 - 符合RoHS指令
 - 工作温度: -20℃~70℃
 - 储存温度: -30℃~80℃
 - 建议TP V.A开窗比LCD A.A单边大0.4mm
 - 泡棉开窗比LCD A.A单边大0.3mm

REV	SIGN	DESCRIPTION	PIC	DATE
A		首次发行	KZH	2023.06.09

PART DESCRIPTION		HUA XIAN JING Display Limited www.huaxianjing.com			
DESIGNED		UNIT mm	SCALE 1.00	3rd ANGLE	SHEET NUMBER 1 of 1
CHECKED		PART NUMBER			DRAWING REV. A
APPROVED		MODEL NAME TFT132B013			PART NUMBER N/A