


FPC弯折示意图  
FPC弯折出货

PIN	DESCR I
1	GND
2	DOP
3	DON
4	GND
5	D1P
6	D1N
7	GND
8	CLKP
9	CLKN
10	GND
11	D2P
12	D2N
13	GND
14	D3P
15	D3N
16	GND
17	GND
18	VCC-1V8
19	VCC-1V8
20	NC
21	NC
22	NC
23	NC
24	RSTB
25	GND
26	NC
27	GND
28	K
29	K
30	GND
31	NC
32	GND
33	GND
34	NC
35	A
36	A
37	GND
38	VDD-3V3
39	VDD-3V3
40	NC

- NOTES:
1. Display: 6.86
  2. VIEWING DIRECTION :ALL
  3. Driver IC: ;LCD:
  4. POL: 上 (T= ) 下 (T= )
  5. STORAGE TEMPERATURE: -20° C TO 70° C, OPERATING TEMPERATURE: -10° C TO 60° C;
  6. BL LED: 15 LEDS, If=20\*5mA; Vf=9.0±0.6V,  
LCM Brghtness: cd/m2(min), Chromaticity:  
X=0.30±0.03, Y=0.31±0.03, UNIFORMITY: 80% (min)
  7. \* CRITICAL DIMENSUON; ( ): REF DIMENSION
  8. GENERAL TOLERANCE: ±0.2mm;
  9. LCD warp is ≤ 0.3;
  10. FPC 基材采用1/3 盎司无胶电解铜
  11. ROHS



LCD型号/类型/分辨率	6.86/IPS/480*1280
视觉方向	ALL
贴片方式	上细磨砂0° /下光90°
驱动IC	FL7707N
LED颗数/连接方式/电流	12-LED/并联/80mA

PART DESCRIPTION	LCM		HUA XIAN JING Display Limited www.huaxianjing.com				
DESIGNED			UNIT mm	SCALE 1.00	3rd ANGLE	SIZE A4	SHEET NUMBER 1 of 1
CHECKED			PART NUMBER				DRAWING REV. A
APPROVED			MODEL NAME				PART NUMBER VER. N/A

REV	SIGN	DESCRIPTION	PIC	DATE
A		首次发行	BILL	2022.11.11