

Hua Xian Jing Group(HXJ Group)
(3 LCD Factory, 27 Production Line, 1300 Workers)

1.Shenzhen HUA XIAN JING Display Limited

Add: 3/F,Bldg.11,Huafeng International Intelligent Building City,Wanle Rd.,Shajing Town,Dist.,518104,Shenzhen,China

2.Gao'an HUA XIAN JING Display Limited

Add: Chengxi Industrial Park,Gao'an City,Jiangxi Province

3.Jiangxi HUA JIA Display Limited

Add: Building 7,No.4 Food Avenue,Information Industry Park,Shanggao County Industrial Park,Yichun City,Jiangxi Province

Contact: Lyna Huang
Website: www.huaxianjing.com

Mob: +86 13632586591
E-mail: sales@huaxianjing.com

Product Range

COB Standard LCD Module	character lcd module: 8x1, 8x2, 16x1, 16x2, 16x4, 20x2, 20x4, 24x2, 40x2, 40x4
	graphic lcd module: 122x32, 128x32, 128x64, 128x128, 192x64, 160x32, 160x64, 160x128, 240x64, 240x128, 320x240
COG	COG lcd display(segment,character and dot matrix): 16x2, 64x48, 128x32, 128x64, 128x128, 132x32, 132x52, 132x58, 160x48, 160x160, 192x64, 240x120, 240x160, 240x128
	COG lcd module(segment,character and dot matrix): 128x64, 192x64, 240x120, 240x160
TFT(square)	0.42"、0.96"、1.06"、1.14"、1.3"、1.44"、1.47"、1.54"、1.77"、1.83"、1.96"、1.99"、2.0"、 2.3"、2.36"、2.4"、2.8"、2.83"、2.86"、2.95"、3.0"、3.13"、3.2"、3.36"、3.45"、3.5"、3.97" 、3.98"、4.3"、4.45"、4.95"、4.96"、5.0"、5.5"、6.75"、6.86"、7"、9.35"、10.11"
TFT(round)	0.9" round、1.2" round、1.28" round、1.32" round、1.38" round、1.46" round、1.6" round、 2.1" round、2.76"round、2.76" round、3.6" round、4.0" round
OLED	0.32"、0.42"、0.49"、0.5"、0.66"、0.69"、0.71"、0.78"、0.87"、0.91"、0.96"、0.96" vertical 、1.3"、1.3" vertical、1.5"、1.54"、0.91" with PCB、0.96" with PCB、1.3" with PCB、1.54" with PCB
Custom segment lcd display and segment lcd module	TN,STN,HTN,FSTN,DFSTN segment lcd or segment lcd module,VA LCD (also can call EBTN)

Marked yellow color for this sheet is popular model number,sell big qty.Except the model number in the sheet,we still have many model number hadn't included in the sheet,we welcome you inquiry with your drawing or requiremnet,we will recommend suitable model number to you according to your requirement.

Standard OLED product List

Size	Product number	Structure	Dot matrix	Panel size(mm)	View area(mm)	Active area size(mm)	Pin Numb	Color (Monochrome)	IC	Interface	connection type
0.32	HP6032-02-TSWG14P032	COG	60x32	9.96x8.85x1.2	8.06x4.82	7.06x3.82	14	White	SSD1315	I2C	soldering
0.42	HP7240-30-TSWG16P042B	COG	72x40	12x11x1.227	10.196x6.18	9.196x5.18	16	White	SSD1315	4-WIRE Serial interface,I2C	soldering
0.42	HP7240-50-TSWG16P042C	COG	72x40	12x11x1.25	10.196x6.18	9.196x5.18	16	White	SSD1315	4-WIRE Serial interface,I2C	soldering
0.49	HP6432-02-TSWG14P049	COG	64x32	14.5x11.6x1.227	12.58x6.98	11.18x5.58	14	White	SSD1306	I2C	socket
0.49	HP6432-20-TSWG14P049B	COG	64x32	14.5x11.6x1.227	12.58x6.98	11.18x5.58	14	White	SSD1315	I2C	soldering
0.5	HP4888-00-TCWG14P050	COG	48x88	8.928x17.1x1.227	7.124x12.244	6.124x11.244	14	White	CH1115		soldering
0.66	HP6448-00-TSWG28P066	COG	64x48	18.46x18.1x1.21	15.42x12.06	13.42x10.06	28	White	SSD1306	6800/8080 Interface/I ² C/ 4-wire SPI	soldering
0.66	HP6448-02-TSWG15P066	COG	64x48	18.46x18.1x1.21	15.42x12.06	13.42x10.06	15	White	SSD1306		socket
0.66	HP6448-05-TSBG28P066	COG	64x48	18.46x18.1x1.21	15.42x12.06	13.42x10.06	28	Blue	SSD1306	6800/8080 Interface/I ² C/ 4-wire SPI	soldering
0.66	HP6448-07-TSWG16P066	COG	64x48	18.46x18.1x1.21	15.42x12.06	13.42x10.06	16	White	SSD1306		socket
0.66	HP6448-10-TSWG16P066	COG	64x48	18.46x18.1x1.21	15.42x12.06	13.42x10.06	16	White	SSD1306		socket
0.69	HP9616-01-TSWG14P069	COG	96x16	26.3x8x1.227	18.86x4.78	17.26x3.18	14	White	SSD1306	I2C	soldering
0.69	HP9616-15-TSWG14P069B	COG	96x16	24x6.9x1.25	18.26x4.18	17.26 x3.18	14	White	SSD1312	I2C	soldering
0.69	HP9616-20-TSWG8P069	COG	96x16	24x6.9x1.25	18.26x4.18	17.26 x3.18	8	White	SSD1306	I2C	socket
0.71	HP4864-01-TSWG14P071	COG	48x64	13.9x22x1.227	12.14x16.3	10.54x14.7	14	White	SSD1306	I2C	soldering
0.71	HP4864-03-TSWG15P071	COG	48x64	13.9x22x1.227	12.14x16.3	10.54x14.7	15	White	SSD1306		socket

Standard OLED product List

Size	Product number	Structure	Dot matrix	Panel size(mm)	View area(mm)	Active area size(mm)	Pin Number	Color (Monochrome)	IC	Interface	connection type
0.78	HP80128-00-THWG13P078	COG	80x128	12.13x23.6x1.227	10.68x18.26	9.68x17.26	13	White	SH1107	4-wire serial interface, I ² C	soldering
0.78	HP80128-09-THWG11P078	COG	80x128	12.13x23.6x1.227	10.68x18.26	9.68x17.26	11	White	SH1107	4-wire serial interface, I2C	socket
0.87	HP12832-00-TSWG15P087	COG	128x32	29x8.7x1.22	22.856x6.824	21.356x5.324	15	White	SSD1316Z	4-wire SPI	socket
0.87	HP12832-05-TSWG14P087	COG	128x32	29x8.7x1.22	22.856x6.824	21.356x5.324	14	White	SSD1316Z	I ² C	soldering
0.91	HP12832-01-TSWG14P091	COG	128x32	30x11.5x1.227	24.384x7.584	22.384x5.584	14	White	SSD1306	I ² C	soldering
0.91	HP12832-02-TSBG12P091	COG	128x32	30x11.5x1.227	24.384x7.584	22.384x5.584	12	Blue	SSD1306	4-wire SPI	soldering
0.91	HP12832-03-TSWG15P091	COG	128x32	30x11.5x1.227	24.384x7.584	22.384x5.584	15	White	SSD1306	4-wire SPI	soldering
0.91	HP12832-04-TSWG15P091	COG	128x32	30x11.5x1.227	24.384x7.584	22.384x5.584	15	White	SSD1306	4-wire SPI	socket
0.91	HP12832-06-TSBG15P091	COG	128x32	30x11.5x1.227	24.384x7.584	22.384x5.584	15	Blue	SSD1306	4-wire SPI	socket
0.91	HP12832-07-TSBG15P091	COG	128x32	30x11.5x1.227	24.384x7.584	22.384x5.584	15	Blue	SSD1306	4-wire SPI	soldering
0.91	HP12832-08-TSBG14P091	COG	128x32	30x11.5x1.227	24.384x7.584	22.384x5.584	14	Blue	SSD1306	I2C	soldering
0.91	HP12832-24-TSWG14P091	COG	128x32	30x11.5x1.227	24.384x7.584	22.384x5.584	14	White	SSD1306	I2C	socket
0.91	HP12832-34-TSWG14P091	COG	128x32	30x11.5x1.227	24.384x7.584	22.384x5.584	14	White	SSD1306		socket
0.91	HP12832-51-TSWG4P091	COG	128x32	30x11.5x1.227	24.384x7.584	22.384x5.584	4	White	SSD1306	I2C	

Standard OLED product List

Size	Product number	Structure	Dot matrix	Panel size(mm)	View area(mm)	Active area size(mm)	Pin Number	Color (Monochrome)	IC	Interface	connection type
0.96	HP12864-03-KSWG30P096	COG	128x64	26.7x19.26x1.41	23.744x12.864	21.744x10.864	30	White	SSD1306	6800/8080 Interface/I ² C/ 4-wire SPI	soldering
0.96	HP12864-04-TSDG30P096	COG	128x64	26.7x19.26x1.41	23.74x13.2	21.74x11.2	30	Yellow & Blue	SSD1306	6800/8080 Interface/I ² C/ 4-wire SPI	soldering
0.96	HP12864-05-KSBG30P096	COG	128x64	26.7x19.26x1.41	23.74x12.864	21.744x10.864	30	Blue	SSD1306	6800/8080 Interface/I ² C/ 4-	soldering
0.96	HP12864-16-KSWG20P096	COG	128x64	26.7x19.26x1.41	23.74x12.864	21.744x10.864	20	White	SSD1306	4 wire serial interface, I2C	socket
0.96	HP12864-21-KSBG30P096	COG	128x64	26.7x19.26x1.41	23.74x12.864	21.744x10.864	30	Blue	SSD1306	6800/8080 interface, 4 wire serial interface, I2C	socket
0.96	HP12864-25-KSWG27P096	COG	128x64	26.7x19.26x1.41	23.74x12.864	21.744x10.864	27	White	SSD1306	6800/8080 interface, 4 wire serial interface, I2C	soldering
0.96	HP12864-31-KSBG15P096	COG	128x64	26.7x19.26x1.41	23.744x12.864	21.744x10.864	15	Blue	SSD1306		soldering
0.96	HP12864-37-KSBG30P096	COG	128x64	26.7x19.26x1.41	23.74x12.864	21.744x10.864	30	Blue	SSD1306	6800/8080 interface, 4 wire serial interface, I2C	socket
0.96	HP12864-51-KSWG30P096	COG	128x64	26.7x19.26x1.41	23.74x12.864	21.744x10.864	30	White	SSD1306		socket
0.96	HP12864-01-KSWG20P096	COG	128x64	24.74x16.9x1.42	22.74x11.86	21.74x10.86	20	White	SSD1315	I ² C/ 3/4-wire SPI	soldering
0.96	HP12864-02-KSWG30P096	COG	128x64	24.74x16.9x1.42	22.74x11.86	21.74x10.86	30	White	SSD1315	I ² C/ 3/4-wire SPI	soldering
0.96	HP12864-06-KSWG30P096	COG	128x64	24.74x16.9x1.42	22.74x11.86	21.74x10.86	30	White	SSD1315	I ² C/ 3/4-wire SPI	soldering

Standard OLED product List

Size	Product number	Structure	Dot matrix	Panel size(mm)	View area(mm)	Active area size(mm)	Pin Number	Color (Monochrome)	IC	Interface	connection type
0.96	HP12864-08-KSWG14P096	COG	128x64	24.74x16.9x1.42	22.74x11.86	21.74x10.86	14	White	SSD1315	4-wire SPI	soldering
0.96	HP12864-09-KSBG30P096	COG	128x64	24.74x16.9x1.42	22.74x11.86	21.74x10.86	30	Blue	SSD1315	I ² C/ 3/4-wire SPI	soldering
0.96	HP12864-43-KSWG30P096	COG	128x64	24.74x16.9x1.42	22.74x11.86	21.74x10.86	30	White	SSD1315	3/4wire serial interface, I2C	socket
0.96 vertical	HP64128-01-THWG13P096	COG	64x128	14x28x1.227	11.86x22.74	10.86x21.74	13	White	SH1107	I ² C/ 4-wire SPI	soldering
0.96 vertical	HP64128-41-TSWG13P096G	COG	64x128	14x28x1.227	11.86x22.74	10.86x21.74	13	White	SSD1312	4-wire serial interface, I2C	soldering
0.96 vertical	HP64128-45-TSWG12P096G	COG	64x128	14x28x1.227	11.86x22.74	10.86x21.74	12	White	SSD1312	4-wire serial interface, I2C	socket
0.96 vertical	HP64128-46-TSWG14P096G	COG	64x128	14x28x1.227	11.86x22.74	10.86x21.74	14	White	SSD1312		socket
0.96 vertical	HP64128-47-TSWG14P096G	COG	64x128	14x28x1.227	11.86x22.74	10.86x21.74	14	White	SSD1312		soldering
0.96 with PCB	HP12864-59-KSWG4P096	COG	128x64	27.5x27.8x2.61	23.74x12.864	21.744x10.864	4	White	SSD1306	I2C	soldering
0.96 with PCB	HP12864-79-KSBG4P096	COG	128x64	27.5x27.8x2.61	23.74x12.864	21.74x10.864	4	Blue	SSD1306	I2C	soldering
0.96 with PCB	HP12864-99-KSWG4P096	COG	128x64	27.5x27.8x2.61	23.74x12.864	21.744x10.864	4	White	SSD1306	I2C	soldering
0.96 with PCB	HP12864-132-KSBG7P096	COG		27.5x27.8x2.61	23.74x12.864	21.744x10.864	7	Blue	SSD1306		soldering
0.96 with PCB	HP12864-160-KSBG4P096	COG	128x64	27.5x27.8x11.5	23.74x12.864	21.744x10.864	4	Blue	SSD1306	I2C	soldering
1.3	HP12864-18-KHWG30P130	COG	128x64	34.5x23x1.427	31.42x16.7	29.42x14.7	30	White	SH1106G	6800/8080 Interface,4-wire serial interface I2C	soldering

Standard OLED product List

Size	Product number	Structure	Dot matrix	Panel size(mm)	View area(mm)	Active area size(mm)	Pin Number	Color (Monochrome)	IC	Interface	connection type
1.3	HP12864-24-KHWG16P130	COG	128x64	34.5x23x1.427	31.42x16.7	29.42x14.7	16	White	SH1106G	4 wire serial interface	socket
1.3	HP12864-36-KHBG30P130	COG	128x64	34.5x23x1.427	31.42x16.7	29.42x14.7	30	Blue	SH1106G	6800/8080 interface, 4 wire serial interface, I2C	soldering
1.3	HP12864-42-KHBG30P130	COG	128x64	34.5x23x1.427	31.42x16.7	29.42x14.7	30	Blue	SH1106G	6800/8080 interface, 4 wire serial interface, I2C	socket
1.3	HP12864-44-KHWG30P130	COG	128x64	34.5x23x1.427	31.42x16.7	29.42x14.7	30	White	SH1106G		socket
1.3	HP12864-134-KHBG16P130	COG	128x64	34.5x23x1.427	31.42x16.7	29.42x14.7	16	Blue	SH1106G	4 wire serial interface	socket
1.3 vertical	HP64128-09-KHWG13P130	COG	64X128	17.1x35.8x1.427	15.3x30.02	14.7x29.42	13	White	SH1107		soldering
1.3 with PCB	HP12864-96-KHWG4P130	COG	128x64	35.5x33.5x2.6	31.42x16.7	29.42x14.7	4	White	SH1106G	SPI	
1.3 with PCB	HP12864-46-KHWG30P130	COG	128x64	35.4x33.5x2.7			8	White	SH1106G & GT20L16S1Y		
1.54	HP12864-12-KPWG24P154	COG	128x64	42.04x27.22x1.41	37.052x19.516	35.052x17.516	24	White	SPD0301ZD	6800/8080 interface, 4 wire serial interface, I2C	socket
1.54	HP12864-32-KPYG24P154	COG	128x64	42.04x27.22x1.41	37.052x19.516	35.052x17.516	24	Yellow	SPD0301ZD	6800/8080 interface, 4 wire serial interface, I2C	socket
1.54	HP12864-48-KPBG24P154	COG	128x64	42.04x27.22x1.41	37.052x19.516	35.052x17.516	24	Blue	SPD0301ZD	6800/8080 interface, 4 wire serial interface, I2C	socket
1.54 with PCB	HP12864-77-KPBG24P154	COG	128x64	42.4x38x2.8	37.05x19.52	35.05x17.52	7	Blue	SPD0301	SPI	