

All Pages Of This Edition Approved

Signature:

Date:

REV.

DESCRIPTION

REVISER





DATE

A0

First

luojinwei

2017-11-07



PIN	SYMBOL
1	NC(GND)
2	C2P
3	C2N
4	C1P
5	C1N
6	VBAT
7	NC
8	VSS
9	VDD
10	BS0
11	BS1
12	BS2
13	CS#
14	RES#
15	D/C#
16	R/W#
17	E#
18	D0
19	D1
20	D2
21	D3
22	D4
23	D5
24	D6
25	D7
26	IREF
27	VCOMH
28	VCC
29	VLSS
30	NC(GND)

Specifications:

1. Display : OLED(BLUE).
2. Dot Matrix: 128*64
3. Dot Size: 0.154*0.154mm
4. Dot Pitch: 0.17*0.17mm
5. Aperture Rate: 78%
6. Active Area : 21.744*10.864mm
7. Drive IC: SSD1306
8. FPC P/N: FPC-HP12864-21-A0



深圳市华显晶显示技术有限公司

HUA XIAN JING Display Limited

www.huaxianjing.com

Unspecified Tolerance:

±0.20

UNITS: mm

DATE:

MODEL NUMBER :

DESIGN BY:

luojinwei


2017-11-07

HP12864-21-KSBG30P096-A

CHECKED BY:

APPROVED BY:

DO NOT SCALE THIS DRAWING.



PROJECTION

SHEET:

1 OF 1

SCALE:

1 : 1