


FPC弯折示意图
FPC展开出货

1	LEDA
2	LEDK
3	VDD
4	GND
5	RST
6	CS
7	SCLK
8	D/C
9	SDA
10	TE

LCD型号/类型/分辨率	HSD1.54/IPS/240*240
视角方向	ALL
偏光片	上磨7° /下光83°
驱动IC	ST7789V2
LED颗数/连接方式/电流	3-LED/并联/60mA

技术要求:

- 带*尺寸为重点尺寸, 带()尺寸为参考尺寸
- LCD切割断面崩边≤1/3 (单层LCD厚度)
- 平面翘曲度≤0.35mm
- 符合RoHS指令
- 工作温度: -20℃~70℃
- 储存温度: -30℃~80℃
- 建议TP V.A开窗比LCD A.A单边大0.4mm
- 泡棉开窗比LCD A.A单边大0.3mm



PART DESCRIPTION	LCM	HUA XIAN JING Display Limited				
DESIGNED		UNIT mm	SCALE 1.00	3rd ANGLE	SIZE A4	SHEET NUMBER 1 of 1
CHECKED		PART NUMBER				DRAWING REV. A
APPROVED		MODEL NAME TFT015H045-A0				PART NUMBER VER. N/A

REV	SI GN	DESCRIPTION	PI C	DATE
A		单层区往下移0.30MM, 其它不变	KZH	2022.08.05
		首次发行	KZH	2022.07.05