



不喷码

展开出货

1	X(L)
2	Y(U)
3	X(R)
4	Y(D)
5	GND
6	IOVCC(1.8V/2.8V)
7	VCI(2.8)
8	FMARK
9	CS/SPI CS
10	RS/A0(4 WIRE)
11	WR/SPI SCL/SCK
12	RD
13	SPI SDI/SDA
14	SPI SDO
15	RESET
16	GND
17	D0
18	D1
19	D2
20	D3
21	D4
22	D5
23	D6
24	D7
25	D8
26	D9
27	D10
28	D11
29	D12
30	D13
31	D14
32	D15
33	A
34	K
35	K
36	K
37	GND
38	IMO
39	IM1
40	IM2

LCD型号/类型/分辨率	CT035TN01/TN/HVGA
视角方向	12 o'Clock
偏光片	上磨45° /下光45°
驱动IC	ST7796U
LED颗数/连接方式/电流	6-LED/90mA
背光底色要求	

- 技术要求:
- 带\*尺寸为重点尺寸, 带 () 尺寸为参考尺寸
  - LCD切割断面崩边≤1/3 (单层LCD厚度)
  - 平面翘曲度≤0.35mm
  - 符合RoHS指令
  - 工作温度: -20℃~70℃
  - 储存温度: -30℃~80℃
  - 建议TP V, A开窗比LCD A, A单边大0.4mm
  - 泡棉开窗比LCD A, A单边大0.3mm

REV	SIGN	DESCRIPTION	PIC	DATE
A		首次发行	KZH	2022.06.27

PART DESCRIPTION	LCM		HUA XIAN JING Display Limited			
DESIGNED			UNIT mm	SCALE 1.00	3rd ANGLE	SHEET NUMBER 1 of 1
CHECKED			PART NUMBER			DRAWING REV. A
APPROVED			MODEL NAME TFT035F056-A0		PART NUMBER VER. N/A	