

FPC展开出货

QSPI


MAIN FPC PIN	DESCRIPTION
1	TP-VCC
2	TP_INT
3	TP_SDA
4	TP_SCL
5	TP_RST
6	GND
7	SPI_CS
8	SPI_IO0
9	SPI_IO3
10	GND
11	SPI_CLK
12	GND
13	SPI_IO1
14	SPI_IO2
15	SPI_RST
16	TE
17	WIRE(NC)
18	GND
19	IO_VCC
20	VCC
21	NC
22	LEDA
23	LEDK
24	MTP_PWR

PIN	DESCRIPTION
1	TP-VCC
2	TP_INT
3	TP_SDA
4	TP_SCL
5	TP_RST
6	GND

LCD型号/类型/分辨率	BOE1.46/IPS/360*360
视觉方向	ALL
贴片方式	上细砂0°/下增亮90°
驱动IC	ST77916
LED颗数/连接方式/电流	

技术要求:

1. 未标注尺寸公差±0.20MM
2. LCD切割断面崩边≤1/3 (单层LCD厚度)
3. 平面翘曲度≤0.35mm
4. 符合RoHS指令
5. 工作温度: -20℃~70℃
6. 储存温度: -30℃~80℃
7. 建议TP V.A开窗比LCD A.A单边大0.4mm
8. 泡棉开窗比LCD A.A单边大0.3mm



REV	SIGN	DESCRIPTION	PIC	DATE
A		首次发行	BILL	2023.04.19

PART DESCRIPTION		HUA XIAN JING Display Limited			
DESIGNED		UNIT	SCALE	3rd ANGLE	SHEET NUMBER
CHECKED		mm	1.00	⊕	1 of 1
APPROVED		PART NUMBER			DRAWING REV.
		MODEL NAME			A
		TFT146B005			PART NUMBER
					N/A