


No.	PIN NAME
1	GND
2	DOP
3	DON
4	GND
5	DIP
6	DIN
7	GND
8	CLKP
9	CLKN
10	GND
11	NC
12	NC
13	GND
14	NC
15	NC
16	GND
17	GND
18	VIDCC
19	VIDCC
20	NC
21	NC
22	NC
23	NC
24	RSTB
25	NC
26	NC
27	GND
28	LED-K
29	LED-K
30	GND
31	NC
32	GND
33	GND
34	NC
35	LED-A
36	LED-A
37	GND
38	VCC
39	VCC
40	NC

FPC弯折后客户参考图
FPC展开出货

LCD型号/类型/分辨率	BOE4.45/1PS/480RGB*854
视角方向	ALL
偏光片	上砂0° / 下光90°
驱动IC	ST7701S
LED颗数/连接方式/电流	10LED/10并/Vf=3.0±0.2V, If=200mA

Circuit Diagram 电路图
(LED 10PCS) Color颜色:WHI TE
Vf=3.0±0.2V, If=200mA



PART DESCRIPTION	LCM	HUA XIAN JING Display Limited			
DESIGNED	UNIT mm	SCALE 1.00	3rd ANGLE	SIZE A4	SHEET NUMBER 1 of 1
CHECKED	PART NUMBER				DRAWING REV. A0
APPROVED	MODEL NAME	TFT445B023			PART NUMBER VER. N/A

		按客户要求FPC展开出货	KZH	2023.10.16
A0		首次发行	KZH	2023.03.03
REV	SIGN	DESCRIPTION	PIC	DATE

- 技术要求:
- 示标注尺寸公差都按±0.2MM
 - LCD切割断面崩边≤1/3 (单层LCD厚度)
 - 平面翘曲度≤0.35mm
 - 符合RoHS指令
 - 工作温度: -20℃~70℃
 - 储存温度: -30℃~80℃
 - 建议TP V. A开窗比LCD A. A单边大0.4mm
 - 泡棉开窗比LCD A. A单边大0.3mm