


NO.	PIN定义
1	GND
2	D0P
3	D0N
4	GND
5	D1P
6	D1N
7	GND
8	CLKP
9	CLKN
10	GND
11	D2P
12	D2N
13	GND
14	D3P
15	D3N
16	GND
17	GND
18	IOVCC
19	IOVCC
20	NC
21	NC
22	NC
23	NC
24	RST
25	NC
26	NC
27	GND
28	K
29	K
30	GND
31	NC
32	GND
33	GND
34	NC
35	A
36	A
37	GND
38	VDD3.3V
39	VDD3.3V
40	NC



分辨率	480*1280
视觉方向	ALL
贴片方式	上细磨砂0° / 下光90°
驱动IC	ICNL9707
LED颗数/连接方式/电流	14-LED/并联/80mA

- NOTES:
- Display: 9.35"
  - VIEWING DIRECTION :ALL
  - Driver IC: ICNL9707
  - POL:上 (T= )下 (T= )
  - OPERATING TEMPERATURE:-20° C TO 70° C  
STORAGE TEMPERATURE: -30° C TO 80° C;
  - BL LED:14 LEDES, If=40\*2mA; Vf=19.2±1.8V,  
LCM Brghtness: cd/m2(min),Chromaticity:  
X=0.30±0.03, Y=0.31±0.03, UNIFORMITY: 80%(min)
  - \* CRITICAL DIMENSUON; ( ) : REF DIMENSION
  - GENERAL TOLERANCE: ±0.2mm;
  - LCD warp is ≤ 0.3;
  - FPC 基材采用1/3 盎司无胶电解铜
  - ROHS

REV	SIGN	DESCRIPTION	PIC	DATE
A		首次发行	RSF	2022.07.15

PART DESCRIPTION	LCM		HUA XIAN JING Display Limited				
DESIGNED	UNIT	SCALE	3rd ANGLE	SIZE	SHEET NUMBER		
CHECKED	mm	1.00	⊕	A4	1 of 1		
APPROVED	PART NUMBER			DRAWING REV.			
	MODEL NAME			PART NUMBER VER.			
	TFT935K009			A			N/A